

TERM PROJECT

Version: 2009-11-25 (there may be other versions later)

The term project involves a 2-D formulation and a 1-D solution of the flow equations described in the next several pages. The term project should stand on its own – feel free to include portions of homework problems. Include anything that you feel will help us know that you understand the material.

- 1) Describe the finite difference formulation for each of the four options in 2-D. Include pictures of 0 and non-zero portions of matrix equations.
- 2) Present the results of your 1-D simulations for option 1, 2, and 4, including a comparison of the different techniques.
- 3) Provide a copy of the source code you used for this project

Option 1: IMPES; Implicit Fracture Pressure, Explicit Saturation, Sequential Method

First, solve for fracture pressure $\Delta_i P_{of}^{n+1}$ using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure P_{om}^{n+1} using an explicit solution of the total matrix flow equation. Next, solve for S_{wf}^{n+1} using an explicit solution of the water saturation equation. Finally, solve for S_{wm}^{n+1} using an explicit solution of the water matrix equation.

Option 2: Implicit Pressure, Partially Implicit Saturation, Sequential Method

First, solve for fracture pressure $\Delta_i P_{of}^{n+1}$ using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure P_{om}^{n+1} using an explicit solution of the total matrix flow equation. Next, solve for $\Delta_i S_{wf}^{n+1}$ using an implicit matrix solution of the water saturation equation. Finally, solve for S_{wm}^{n+1} using an explicit solution of the water matrix equation.

Option 3: Fully Implicit; Iterative

First, solve for fracture pressure $\delta P_{of}^{\ell+1}$ using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure $P_{om}^{\ell+1}$ using an explicit solution of the total matrix flow equation. Next, solve for $\delta S_{wf}^{\ell+1}$ using an implicit matrix solution of the water saturation equation. Finally, solve for $S_{wm}^{\ell+1}$ using an explicit solution of the water matrix equation. Repeat the iterations until convergence is obtained, calculating first $P_o^{\ell+1}$ using the values of P_{om}^{ℓ} , S_{wf}^{ℓ} , and S_{wm}^{ℓ} . Next, solve for $P_{om}^{\ell+1}$ using the values of $P_o^{\ell+1}$, S_{wf}^{ℓ} , and S_{wm}^{ℓ} . Third, solve for $S_{wf}^{\ell+1}$ using the values of $P_o^{\ell+1}$, $P_{om}^{\ell+1}$, and S_{wm}^{ℓ} . Finally, solve for $S_{wm}^{\ell+1}$ using the values of $P_o^{\ell+1}$, $P_{om}^{\ell+1}$, and $S_{wf}^{\ell+1}$.

Option 4: Fully Implicit; Simultaneous

Solve simultaneously for δP_{of}^{n+1} , δP_{om}^{n+1} , δS_{wf}^{n+1} , and δS_{wm}^{n+1} using a Newton-Raphson formulation.

Option 1: IMPES; Implicit Fracture Pressure, Sequential Matrix Pressure, Sequential Saturation

First, solve for fracture pressure P_{of}^{n+1} using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure P_{om}^{n+1} using an explicit solution of the total matrix flow equation. Next, solve for S_{wf}^{n+1} using an explicit solution of the water saturation equation. Finally, solve for S_{wm}^{n+1} using an explicit solution of the water matrix equation.

Fracture Pressure Equation:

$$\nabla \cdot \left(k_{f,eff} \left(\lambda_{Tf}^n \nabla P_{of}^{n+1} - \left(\lambda_{wf}^n \gamma_w^n + \lambda_{of}^n \gamma_o^n \right) \nabla D - \lambda_{wf}^n \nabla P_{cwo}^n \right) \right) - \tau_T^{n+1} + \hat{q}_{Tf}^{n+1} = \phi_f C_{Tf} \frac{P_{of}^{n+1} - P_{of}^n}{\Delta t}$$

Total Transfer:

$$\tau_T^{n+1} = \sigma k_m \left(\lambda_{Tf}^n (P_{of}^{n+1} - P_{om}^{n+1}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^n \gamma_w^n + \lambda_{om/f}^n \gamma_o^n) (h_{wf}^n - h_{wm}^n) + \lambda_{wf/m}^n (P_{cwom}^n - P_{cwof}^n) \right)$$

Total Matrix flow:

$$\tau_T^{n+1} = \phi_m C_{Tm} \frac{P_{om}^{n+1} - P_{om}^n}{\Delta t}$$

Saturation equation, explicit (IMPES):

$$\nabla \cdot \left(k_{f,eff} \left(\lambda_{wf}^n \nabla P_{of}^{[n+1]} - \left(\lambda_{wf}^n \gamma_w^n \right) \nabla D - \lambda_{wf}^n \nabla P_{cwo}^n \right) \right) - \tau_w^{[n+1]} + \hat{q}_{wf}^{[n+1]} = \phi_f S_{wf}^{n+1} (C_{\phi_f} + C_{wf}) \frac{P_{of}^{[n+1]} - P_{of}^n}{\Delta t} + \phi \frac{S_{wf}^{n+1} - S_{wf}^n}{\Delta t}$$

Water Transfer:

$$\tau_w^{[n+1]} = \sigma k_m \left(\lambda_{wf}^n (P_{of}^{[n+1]} - P_{om}^{[n+1]}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^n \gamma_w^n) (h_{wf}^n - h_{wm}^n) + \lambda_{wf/m}^n (P_{cwom}^n - P_{cwof}^n) \right)$$

Water Total Matrix flow:

$$\tau_w^{[n+1]} = \phi_m S_{wm}^{n+1} (C_{\phi_m} + C_{wm}) \frac{P_{om}^{[n+1]} - P_{om}^n}{\Delta t} + \phi \frac{S_{wm}^{n+1} - S_{wm}^n}{\Delta t}$$

Option 2: Partially Implicit; Implicit Pressure, Sequential Saturation

First, solve for fracture pressure P_{of}^{n+1} using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure P_{om}^{n+1} using an explicit solution of the total matrix flow equation. Next, solve for S_{wf}^{n+1} using an implicit matrix solution of the water saturation equation. Finally, solve for S_{wm}^{n+1} using an explicit solution of the water matrix equation.

Fracture Pressure Equation:

$$\nabla \cdot \left(k_{f,eff} \left(\lambda_{Tf}^n \nabla P_{of}^{n+1} - \left(\lambda_{wf}^n \gamma_w^n + \lambda_{of}^n \gamma_o^n \right) \nabla D - \lambda_{wf}^n \nabla P_{cwo}^n \right) \right) - \tau_T^{n+1} + \hat{q}_{Tf}^{n+1} = \phi_f C_{Tf} \frac{P_{of}^{n+1} - P_{of}^n}{\Delta t}$$

Total Transfer:

$$\tau_T^{n+1} = \sigma k_m \left(\lambda_{Tf}^n (P_{of}^{n+1} - P_{om}^{n+1}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^n \gamma_w^n + \lambda_{om/f}^n \gamma_o^n) (h_{wf}^n - h_{wm}^n) + \lambda_{wf/m}^n (P_{cwom}^n - P_{cwof}^n) \right)$$

Total Matrix flow:

$$\tau_T^{n+1} = \phi_m C_{Tm} \frac{P_{om}^{n+1} - P_{om}^n}{\Delta t}$$

Saturation equation, explicit:

$$\nabla \cdot \left(k_{f,eff} \lambda_{wf}^n \left(\nabla P_{of}^{[n+1]} - \gamma_w^n \nabla D - \frac{\partial P_{cwof}^n}{\partial S_{wf}} \nabla S_{wf}^{n+1} \right) \right) - \tau_w^{[n+1]} + \hat{q}_{wf}^{[n+1]} = \phi_f S_{wf}^n (C_{\phi_f} + C_{wf}) \frac{P_{of}^{[n+1]} - P_{of}^n}{\Delta t} + \phi \frac{S_{wf}^{n+1} - S_{wf}^n}{\Delta t}$$

Water Transfer:

$$\tau_w^{[n+1]} = \sigma k_m \left(\lambda_{wf}^n (P_{of}^{[n+1]} - P_{om}^{[n+1]}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^n \gamma_w^n) (h_{wf}^n - h_{wm}^n) + \lambda_{wf/m}^n (P_{cwom}^n - P_{cwof}^n) \right)$$

Water Total Matrix flow:

$$\tau_w^{[n+1]} = \phi_m S_{wm}^{n+1} (C_{\phi_m} + C_{wm}) \frac{P_{om}^{[n+1]} - P_{om}^n}{\Delta t} + \phi \frac{S_{wm}^{n+1} - S_{wm}^n}{\Delta t}$$

Option 3: Fully Implicit; Iterative

First, solve for fracture pressure $P_{of}^{\ell+1}$ using the implicit fracture flow equation in matrix form. Next, solve for the matrix pressure $P_{om}^{\ell+1}$ using an explicit solution of the total matrix flow equation. Next, solve for $S_{wf}^{\ell+1}$ using an implicit matrix solution of the water saturation equation. Finally, solve for $S_{wm}^{\ell+1}$ using an explicit solution of the water matrix equation. Repeat the iterations until convergence is obtained, calculating first $P_o^{\ell+1}$ using the values of P_{om}^{ℓ} , S_{wf}^{ℓ} , and S_{wm}^{ℓ} . Next, solve for $P_{om}^{\ell+1}$ using the values of $P_o^{\ell+1}$, S_{wf}^{ℓ} , and S_{wm}^{ℓ} . Third, solve for $S_{wf}^{\ell+1}$ using the values of $P_o^{\ell+1}$, $P_{om}^{\ell+1}$, and S_{wm}^{ℓ} . Finally, solve for $S_{wm}^{\ell+1}$ using the values of $P_o^{\ell+1}$, $P_{om}^{\ell+1}$, and $S_{wf}^{\ell+1}$.

Fracture Pressure Equation:

$$\nabla \cdot \left(k_{f,eff} \left(\lambda_{Tf}^{[n+1]} \nabla P_{of}^{n+1} - \left(\lambda_{wf}^{[n+1]} \gamma_w^{[n+1]} + \lambda_{of}^{[n+1]} \gamma_o^{[n+1]} \right) \nabla D - \lambda_{wf}^{[n+1]} \nabla P_{cwo}^{[n+1]} \right) \right) - \tau_T^{n+1} + \hat{q}_{Tf}^{n+1} = \phi_f C_{Tf}^{[n+1]} \frac{P_{of}^{n+1} - P_{of}^n}{\Delta t}$$

Total Transfer:

$$\tau_T^{n+1} = \sigma k_m \left(\lambda_{Tf}^{[n+1]} (P_{of}^{n+1} - P_{om}^{n+1}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^{[n+1]} \gamma_w^{[n+1]} + \lambda_{om/f}^{[n+1]} \gamma_o^{[n+1]}) (h_{wf}^{[n+1]} - h_{wm}^{[n+1]}) + \lambda_{wf/m}^{[n+1]} (P_{cwo}^{[n+1]} - P_{cwof}^{[n+1]}) \right)$$

Total Matrix flow:

$$\tau_T^{n+1} = \phi_m C_{Tm}^{[n+1]} \frac{P_{om}^{n+1} - P_{om}^n}{\Delta t}$$

Saturation equation, explicit:

$$\nabla \cdot \left(k_{f,eff} \lambda_{wf}^{n+1} \left(\nabla P_{of}^{[n+1]} - \gamma_w^{[n+1]} \nabla D - \frac{\partial P_{cowf}^n}{\partial S_{wf}} \nabla S_{wf}^{n+1} \right) \right) - \tau_w^{[n+1]} + \hat{q}_{wf}^{[n+1]} = \phi_f S_{wf}^{n+1} (C_{\phi_f} + C_{wf}) \frac{P_{of}^{[n+1]} - P_{of}^n}{\Delta t} + \phi \frac{S_{wf}^{n+1} - S_{wf}^n}{\Delta t}$$

Water Transfer:

$$\tau_w^{[n+1]} = \sigma k_m \left(\lambda_{wf}^{[n+1]} (P_{of}^{[n+1]} - P_{om}^{[n+1]}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^{[n+1]} \gamma_w^{[n+1]}) (h_{wf}^{[n+1]} - h_{wm}^{[n+1]}) + \lambda_{wf/m}^{[n+1]} (P_{cwo}^{[n+1]} - P_{cwof}^{[n+1]}) \right)$$

Water Total Matrix flow:

$$\tau_w^{[n+1]} = \phi_m S_{wm}^{n+1} (C_{\phi_m} + C_{wm}) \frac{P_{om}^{[n+1]} - P_{om}^n}{\Delta t} + \phi \frac{S_{wm}^{n+1} - S_{wm}^n}{\Delta t}$$

Option 4: Fully Implicit; Simultaneous

Solve simultaneously for P_{of}^{n+1} , P_{om}^{n+1} , S_{wf}^{n+1} , and S_{wm}^{n+1} .

Water Saturation equation:

$$\nabla \cdot \left(k_{f,eff} \lambda_{wf}^{n+1} \left(\nabla P_{of}^{n+1} - \gamma_w^n \nabla D - \nabla P_{cowf}^{n+1} \right) \right) - \tau_w^{n+1} + \hat{q}_{wf}^{n+1} = \phi_f S_{wf}^{n+1} (C_{\phi_f} + C_{wf}) \frac{P_{of}^{n+1} - P_{of}^n}{\Delta t} + \phi \frac{S_{wf}^{n+1} - S_{wf}^n}{\Delta t}$$

Water Transfer:

$$\tau_w^{n+1} = \sigma k_m \left(\lambda_{wf/m}^{n+1} (P_{of}^{n+1} - P_{om}^{n+1}) + \frac{\sigma_z}{\sigma} (\lambda_{wf/m}^{n+1} \gamma_w^n) (h_{wf}^{n+1} - h_{wm}^{n+1}) + \lambda_{wf/m}^{n+1} (P_{cwom}^{n+1} - P_{cowf}^{n+1}) \right)$$

Water Matrix flow:

$$\tau_w^{n+1} = \phi_m S_{wm}^{n+1} (C_{\phi_m} + C_{wm}) \frac{P_{om}^{n+1} - P_{om}^n}{\Delta t} + \phi \frac{S_{wm}^{n+1} - S_{wm}^n}{\Delta t}$$

Oil Saturation equation:

$$\nabla \cdot \left(k_{f,eff} \lambda_{of}^{n+1} \left(\nabla P_{of}^{n+1} - \gamma_o^n \nabla D \right) \right) - \tau_o^{n+1} + \hat{q}_{of}^{n+1} = \phi_f S_{of}^{n+1} (C_{\phi_f} + C_{wf}) \frac{P_{of}^{n+1} - P_{of}^n}{\Delta t} + \phi \frac{S_{of}^{n+1} - S_{of}^n}{\Delta t}$$

Oil Transfer:

$$\tau_o^{n+1} = \sigma k_m \left(\lambda_{om/f}^{n+1} (P_{of}^{n+1} - P_{om}^{n+1}) + \frac{\sigma_z}{\sigma} (\lambda_{om/f}^{n+1} \gamma_o^n) (h_{wf}^{n+1} - h_{wm}^{n+1}) \right)$$

Oil Matrix flow:

$$\tau_o^{n+1} = \phi_m S_{om}^{n+1} (C_{\phi_m} + C_{wm}) \frac{P_{om}^{n+1} - P_{om}^n}{\Delta t} + \phi \frac{S_{om}^{n+1} - S_{om}^n}{\Delta t}$$

Capillary pressure and relative permeability equations:

$$k_{row} = k_{row}^* \left(\frac{S_o - S_{owr}}{1 - S_{wr} - S_{owr}} \right)^{n_{ow}} \quad k_{rw} = k_{rw}^* \left(\frac{S_w - S_{wr}}{1 - S_{wr} - S_{owr}} \right)^{n_w}$$

$$P_{cow1} = \alpha \ln \left[\frac{1 - S_w - S_{owr}}{1 - S_{wx} - S_{owr}} \right] \quad P_{cow2} = -\alpha \ln \left[\frac{S_w - S_{wr}}{S_{wx} - S_{wr}} \right]$$

$$P_{cow} = \begin{cases} P_{cow,max}, & S_w \leq S_{wr} \\ P_{cow,min}, & S_w \geq (1 - S_{owr}) \\ \min[P_{cow2}, P_{cow,max}], & S_{wr} \leq S_w \leq S_{wx} \\ \max[P_{cow1}, P_{cow,min}], & (1 - S_{owr}) \geq S_w \geq S_{wx} \end{cases}$$

Data:

$$k_{rwm}^* = 0.1 \quad k_{rowm}^* = 0.7 \quad n_{wm} = 1.5 \quad n_{owm} = 2.5 \quad S_{owrm} = 0.30 \quad S_{wrm} = 0.25$$

$$k_{rwf}^* = 0.8 \quad k_{rowf}^* = 0.8 \quad n_{wf} = 2.0 \quad n_{owf} = 2.0 \quad S_{owrf} = 0.05 \quad S_{wrf} = 0.05$$

$$\alpha_m = 0.8; \quad S_{wxm} = 0.5 \quad P_{cowm}^{max} = +5 \text{ psi} \quad P_{cowm}^{min} = -5 \text{ psi}$$

$$\alpha_f = 0.08; \quad S_{wxf} = 0.5 \quad P_{cowf}^{max} = +0.5 \text{ psi} \quad P_{cowf}^{min} = -0.5 \text{ psi}$$

$$\mu_w = 0.6 \text{ cp} \quad \mu_o = 2.4 \text{ cp} \quad \gamma_w = 0.433 \text{ psi / ft} \quad \gamma_o = 0.433 * 0.8 \text{ psi / ft}$$

$$k_m = 10 \text{ md} \quad \phi_m = 0.20 \quad C_{Tm} = 10 \cdot 10^{-6} \text{ psi}^{-1}$$

$$w_f = 50 \mu\text{m} \text{ (convert to feet; use to calculate } \phi_f \text{ and } k_f) \quad u_{Tf} = 25 \text{ ft / day}$$

$$L_x = 10 \text{ feet} \quad L_y = 10 \text{ feet} \quad L_z = 30 \text{ feet}$$

$$\Delta x = 100 \text{ feet} \quad \Delta y = 100 \text{ feet} \quad \Delta z = 30 \text{ feet} \quad IMAX = 10$$

$$P_{of}^{init} = 3000 \text{ psia}, \quad P_{WB,f}^{all} = 2500 \text{ psia}, \quad S_{wf}^{init} = S_{wfr}, \quad S_{wm}^{init} = S_{wmr}$$

$$C_{\phi_f} = 5 \cdot 10^{-6} \text{ psi}^{-1}, \quad C_{\phi_m} = 3 \cdot 10^{-6} \text{ psi}^{-1}, \quad C_w = 4 \cdot 10^{-6} \text{ psi}^{-1}, \quad C_o = 10 \cdot 10^{-6} \text{ psi}^{-1}$$