

Differential Game Theory & Pedestrian Traffic

Andrew Glaws

April 23rd, 2015

Outline

- 1 Control Theory and Differential Games
- 2 Hamiltonian and the Maximum Principle
- 3 1D Example
- 4 Pedestrian Traffic Model
- 5 2D Examples
- 6 Model Parameters
- 7 Future Work

Control Theory

Standard problem in control theory:

- state variable, $\mathbf{x} \in \mathbb{R}^m$
- initial set, \mathbf{X}_0 , and target set, \mathbf{X}_1
- control variable, $\mathbf{u} \in \mathcal{U} \subset \mathbb{R}^n$
 - \mathcal{U} = set of all admissible controls
- system dynamics

$$\begin{cases} \dot{\mathbf{x}} = \mathbf{f}(t, \mathbf{x}, \mathbf{u}) \\ \mathbf{x}(t_0) = \mathbf{x}_0 \in \mathbf{X}_0 \end{cases}$$

- cost functional

$$J(\mathbf{u}) = \psi(\mathbf{x}(t_1)) + \int_{t_0}^{t_1} L(s, \mathbf{x}, \mathbf{u}) ds$$

Control Theory

Standard problem in control theory:

- state variable, $\mathbf{x} \in \mathbb{R}^m$
- initial set, \mathbf{X}_0 , and target set, \mathbf{X}_1
- control variable, $\mathbf{u} \in \mathcal{U} \subset \mathbb{R}^n$
 - \mathcal{U} = set of all admissible controls
- system dynamics

$$\begin{cases} \dot{\mathbf{x}} = \mathbf{f}(t, \mathbf{x}, \mathbf{u}) \\ \mathbf{x}(t_0) = \mathbf{x}_0 \in \mathbf{X}_0 \end{cases}$$

- cost functional

$$J(\mathbf{u}) = \psi(\mathbf{x}(t_1)) + \int_{t_0}^{t_1} L(s, \mathbf{x}, \mathbf{u}) ds$$

Goal: Find the optimal control $\mathbf{u}^* \in \mathcal{U}$ which minimizes the cost functional

$$J(\mathbf{u}^*) \leq J(\mathbf{u}) \quad \text{for all } \mathbf{u} \in \mathcal{U}$$

Differential Game Theory

Definition (Differential Game)

A control theory problem with multiple controls, each operated by a different player who is attempting to minimize their own cost functional, is called a differential game.

Differential Game Theory

Definition (Differential Game)

A control theory problem with multiple controls, each operated by a different player who is attempting to minimize their own cost functional, is called a differential game.

Two-Player Game

System dynamics:

$$\dot{\mathbf{x}} = \mathbf{f}(t, \mathbf{x}, \mathbf{u}_1, \mathbf{u}_2)$$

Cost functionals:

$$J_1(\mathbf{u}_1) = \psi_1(\mathbf{x}(t_1)) + \int_{t_0}^{t_1} L_1(s, \mathbf{x}, \mathbf{u}_1, \mathbf{u}_2) ds$$

$$J_2(\mathbf{u}_2) = \psi_2(\mathbf{x}(t_1)) + \int_{t_0}^{t_1} L_2(s, \mathbf{x}, \mathbf{u}_1, \mathbf{u}_2) ds$$

Differential Game Theory

Differential games appear in a variety of applications:

- Flight and rocket/missile control
- Political science
- Economics and business management
- Military strategy
- Traffic

Differential Game Theory

Differential games appear in a variety of applications:

- Flight and rocket/missile control
- Political science
- Economics and business management
- Military strategy
- Traffic

and take a variety of forms:

- Cooperative vs. non-cooperative games
- Open-loop vs. closed-loop games
- Sequential-move vs. simultaneous-move games
- Zero-sum vs. nonzero-sum games
- Pursuit-evasion games

The Hamiltonian

Definition (Hamiltonian)

Define $\lambda \in \mathbb{R}^m$ where $\lambda = \lambda(t)$ to be the adjoint system. Then, the Hamiltonian is given by

$$H(t, \mathbf{x}(t), \lambda(t), \mathbf{u}(t)) = L(t, \mathbf{x}, \mathbf{u}) + [\lambda(t)]^T \mathbf{f}(t, \mathbf{x}, \mathbf{u}).$$

The Hamiltonian

Definition (Hamiltonian)

Define $\lambda \in \mathbb{R}^m$ where $\lambda = \lambda(t)$ to be the adjoint system. Then, the Hamiltonian is given by

$$H(t, \mathbf{x}(t), \lambda(t), \mathbf{u}(t)) = L(t, \mathbf{x}, \mathbf{u}) + [\lambda(t)]^T \mathbf{f}(t, \mathbf{x}, \mathbf{u}).$$

The state and adjoint dynamics are given by

$$\dot{\mathbf{x}} = \frac{\partial H}{\partial \lambda} \quad \text{and} \quad \dot{\lambda} = -\frac{\partial H}{\partial \mathbf{x}}$$

with $\mathbf{x}(t_0) = \mathbf{x}_0$ and $\mathbf{x}(t_1) \in \mathbf{X}_1$.

The Hamiltonian

Definition (Hamiltonian)

Define $\lambda \in \mathbb{R}^m$ where $\lambda = \lambda(t)$ to be the adjoint system. Then, the Hamiltonian is given by

$$H(t, \mathbf{x}(t), \lambda(t), \mathbf{u}(t)) = L(t, \mathbf{x}, \mathbf{u}) + [\lambda(t)]^T \mathbf{f}(t, \mathbf{x}, \mathbf{u}).$$

The state and adjoint dynamics are given by

$$\dot{\mathbf{x}} = \frac{\partial H}{\partial \lambda} \quad \text{and} \quad \dot{\lambda} = -\frac{\partial H}{\partial \mathbf{x}}$$

with $\mathbf{x}(t_0) = \mathbf{x}_0$ and $\mathbf{x}(t_1) \in \mathbf{X}_1$.

Definition (Transversality Condition)

Let \mathbf{T}_0 and \mathbf{T}_1 be the tangent spaces to \mathbf{X}_0 and \mathbf{X}_1 , respectively. Then,

$$\lambda^*(t_0) \perp \mathbf{T}_0 \quad \text{and} \quad \lambda^*(t_1) \perp \mathbf{T}_1.$$

Pontryagin Maximum Principle

Theorem (Pontryagin Maximum Principle)

Let $\mathbf{u}^ \in \mathcal{U}$ be the optimal control with corresponding optimal state \mathbf{x}^* and optimal adjoint λ^* . Then, \mathbf{u}^* minimizes the Hamiltonian.*

$$H(t, \mathbf{x}^*, \lambda^*, \mathbf{u}^*) \leq H(t, \mathbf{x}^*, \lambda^*, \mathbf{u}) \quad \text{for any } \mathbf{u} \in \mathcal{U}$$

Pontryagin Maximum Principle

Theorem (Pontryagin Maximum Principle)

Let $\mathbf{u}^ \in \mathcal{U}$ be the optimal control with corresponding optimal state \mathbf{x}^* and optimal adjoint λ^* . Then, \mathbf{u}^* minimizes the Hamiltonian.*

$$H(t, \mathbf{x}^*, \lambda^*, \mathbf{u}^*) \leq H(t, \mathbf{x}^*, \lambda^*, \mathbf{u}) \quad \text{for any } \mathbf{u} \in \mathcal{U}$$

Thus,

$$\left. \frac{\partial H}{\partial \mathbf{u}} \right|_{\mathbf{u}=\mathbf{u}^*} = \mathbf{0}$$

1D Example

Consider the one-dimensional domain $\Omega = (0, 1)$ with a single pedestrian.

$$\mathbf{x}(t) = \begin{bmatrix} r(t) \\ v(t) \end{bmatrix},$$

$$\mathbf{x}_0 = \left\{ \begin{bmatrix} 0 \\ 0 \end{bmatrix} \right\}, \quad \mathbf{x}_1 = \left\{ \begin{bmatrix} 1 \\ \alpha \end{bmatrix} \right\}, \text{ where } \alpha \in \mathbb{R},$$

1D Example

Consider the one-dimensional domain $\Omega = (0, 1)$ with a single pedestrian.

$$\mathbf{x}(t) = \begin{bmatrix} r(t) \\ v(t) \end{bmatrix},$$

$$\mathbf{x}_0 = \left\{ \begin{bmatrix} 0 \\ 0 \end{bmatrix} \right\}, \quad \mathbf{x}_1 = \left\{ \begin{bmatrix} 1 \\ \alpha \end{bmatrix} \right\}, \text{ where } \alpha \in \mathbb{R},$$

$$\mathcal{U} = \{u(t) \in \mathbb{R} : u \text{ steers } \mathbf{x} \text{ to } \mathbf{x}_1\},$$

$$\begin{cases} \dot{\mathbf{x}}(t) = \begin{bmatrix} v(t) \\ u(t) \end{bmatrix} \\ \mathbf{x}(t_0) = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \end{cases}$$

1D Example

Consider the one-dimensional domain $\Omega = (0, 1)$ with a single pedestrian.

$$\mathbf{x}(t) = \begin{bmatrix} r(t) \\ v(t) \end{bmatrix},$$

$$\mathbf{x}_0 = \left\{ \begin{bmatrix} 0 \\ 0 \end{bmatrix} \right\}, \quad \mathbf{x}_1 = \left\{ \begin{bmatrix} 1 \\ \alpha \end{bmatrix} \right\}, \text{ where } \alpha \in \mathbb{R},$$

$$\mathcal{U} = \{u(t) \in \mathbb{R} : u \text{ steers } \mathbf{x} \text{ to } \mathbf{x}_1\},$$

$$\begin{cases} \dot{\mathbf{x}}(t) = \begin{bmatrix} v(t) \\ u(t) \end{bmatrix} \\ \mathbf{x}(t_0) = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \end{cases}$$

$$J(u) = \int_0^t \frac{1}{2} \left([u(t)]^2 + 1 \right) ds$$

1D Example

Consider the one-dimensional domain $\Omega = (0, 1)$ with a single pedestrian.

$$\mathbf{x}(t) = \begin{bmatrix} r(t) \\ v(t) \end{bmatrix},$$

$$\mathbf{x}_0 = \left\{ \begin{bmatrix} 0 \\ 0 \end{bmatrix} \right\}, \quad \mathbf{x}_1 = \left\{ \begin{bmatrix} 1 \\ \alpha \end{bmatrix} \right\}, \text{ where } \alpha \in \mathbb{R},$$

$$\mathcal{U} = \{u(t) \in \mathbb{R} : u \text{ steers } \mathbf{x} \text{ to } \mathbf{x}_1\},$$

$$\begin{cases} \dot{\mathbf{x}}(t) = \begin{bmatrix} v(t) \\ u(t) \end{bmatrix} \\ \mathbf{x}(t_0) = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \end{cases}$$

$$J(u) = \int_0^t \frac{1}{2} \left([u(t)]^2 + 1 \right) ds$$

Notice that t_1 is not specified.

1D Example

The Hamiltonian is given by

$$H(t, \mathbf{x}(t), \boldsymbol{\lambda}(t), u(t)) = \frac{1}{2} \left([u(t)]^2 + 1 \right) + \lambda_1(t)v(t) + \lambda_2(t)u(t)$$

1D Example

The Hamiltonian is given by

$$H(t, \mathbf{x}(t), \boldsymbol{\lambda}(t), u(t)) = \frac{1}{2} \left([u(t)]^2 + 1 \right) + \lambda_1(t)v(t) + \lambda_2(t)u(t)$$

System of ODEs:

$$\begin{cases} \dot{r}(t) = v(t) & r(0) = 0 \\ \dot{v}(t) = u(t) & v(0) = 0 \\ \dot{\lambda}_1(t) = 0 & r(t_1) = 1 \\ \dot{\lambda}_2(t) = -\lambda_1(t) & \lambda_2(t_1) = 0 \end{cases}$$

1D Example

The Hamiltonian is given by

$$H(t, \mathbf{x}(t), \boldsymbol{\lambda}(t), u(t)) = \frac{1}{2} \left([u(t)]^2 + 1 \right) + \lambda_1(t)v(t) + \lambda_2(t)u(t)$$

System of ODEs:

$$\begin{cases} \dot{r}(t) = v(t) & r(0) = 0 \\ \dot{v}(t) = u(t) & v(0) = 0 \\ \dot{\lambda}_1(t) = 0 & r(t_1) = 1 \\ \dot{\lambda}_2(t) = -\lambda_1(t) & \lambda_2(t_1) = 0 \end{cases}$$

Maximum Principle:

$$\frac{\partial H}{\partial u}(t, \mathbf{x}^*(t), \boldsymbol{\lambda}^*(t), u^*(t)) = u^*(t) + \lambda_2^*(t) = 0$$


$$\Rightarrow u^*(t) = -\lambda_2^*(t)$$

1D Example

Solution:

$$\begin{cases} r^*(t) = \frac{1}{6\sqrt{3}} (\sqrt{3} - t)^3 + \frac{\sqrt{3}}{2} t - \frac{1}{2} \\ v^*(t) = -\frac{1}{2\sqrt{3}} (\sqrt{3} - t)^2 + \frac{\sqrt{3}}{2} \\ \lambda_1^*(t) = -\frac{1}{\sqrt{3}} \\ \lambda_2^*(t) = -\frac{1}{\sqrt{3}} (\sqrt{3} - t) \end{cases}$$

$$\Rightarrow u^*(t) = -\lambda_2^*(t) = \frac{1}{\sqrt{3}} (\sqrt{3} - t)$$



Pedestrian Traffic Model

Assumptions:

- 1 Pedestrians continuously observe the current state and update their plan

Pedestrian Traffic Model

Assumptions:

- 1 Pedestrians continuously observe the current state and update their plan
- 2 Pedestrians have perfect knowledge of the current state

Pedestrian Traffic Model

Assumptions:

- 1 Pedestrians continuously observe the current state and update their plan
- 2 Pedestrians have perfect knowledge of the current state
- 3 Pedestrians have limited prediction capabilities

Pedestrian Traffic Model

Assumptions:

- 1 Pedestrians continuously observe the current state and update their plan
- 2 Pedestrians have perfect knowledge of the current state
- 3 Pedestrians have limited prediction capabilities
- 4 Pedestrians work harder to avoid groups than individuals

Pedestrian Traffic Model

Assumptions:

- ① Pedestrians continuously observe the current state and update their plan
- ② Pedestrians have perfect knowledge of the current state
- ③ Pedestrians have limited prediction capabilities
- ④ Pedestrians work harder to avoid groups than individuals
- ⑤ Pedestrians' cost functional is made up of 3 components:
 - straying from the optimal velocity
 - discomfort from walking too near to other pedestrians
 - accelerating/decelerating/turning

Pedestrian Traffic Model

System state:

$$\mathbf{x}(t) = \begin{bmatrix} \mathbf{r}_1(t) \\ \vdots \\ \mathbf{r}_N(t) \\ \mathbf{v}_1(t) \\ \vdots \\ \mathbf{v}_N(t) \end{bmatrix}$$

System dynamics:

$$\dot{\mathbf{x}} = \begin{bmatrix} \mathbf{v}_1 \\ \vdots \\ \mathbf{v}_N \\ \mathbf{u}_1 + \mathbf{w}_1 \\ \vdots \\ \mathbf{u}_N + \mathbf{w}_N \end{bmatrix}$$

Pedestrian Traffic Model

System state:

$$\mathbf{x}(t) = \begin{bmatrix} \mathbf{r}_1(t) \\ \vdots \\ \mathbf{r}_N(t) \\ \mathbf{v}_1(t) \\ \vdots \\ \mathbf{v}_N(t) \end{bmatrix}$$

System dynamics:

$$\dot{\mathbf{x}} = \begin{bmatrix} \mathbf{v}_1 \\ \vdots \\ \mathbf{v}_N \\ \mathbf{u}_1 + \mathbf{w}_1 \\ \vdots \\ \mathbf{u}_N + \mathbf{w}_N \end{bmatrix}$$

$\Rightarrow \mathbf{u}_p$ = controllable portion of pedestrian p 's acceleration

$\Rightarrow \mathbf{w}_p$ = uncontrollable portion of pedestrian p 's acceleration

Pedestrian Traffic Model

System state:

$$\mathbf{x}(t) = \begin{bmatrix} \mathbf{r}_1(t) \\ \vdots \\ \mathbf{r}_N(t) \\ \mathbf{v}_1(t) \\ \vdots \\ \mathbf{v}_N(t) \end{bmatrix}$$

System dynamics:

$$\dot{\mathbf{x}} = \begin{bmatrix} \mathbf{v}_1 \\ \vdots \\ \mathbf{v}_N \\ \mathbf{u}_1 + \mathbf{w}_1 \\ \vdots \\ \mathbf{u}_N + \mathbf{w}_N \end{bmatrix}$$

$\Rightarrow \mathbf{u}_p$ = controllable portion of pedestrian p 's acceleration

$\Rightarrow \mathbf{w}_p$ = uncontrollable portion of pedestrian p 's acceleration

$$\begin{aligned} \mathbf{w}_p = \mathbf{w}_{\text{bound}} + \sum_{q \neq p} & \left[k_{p,1} \left((R_p^* + R_q^*) - R_{p,q} \right)^+ \mathbf{n}_{pq} \right. \\ & \left. + k_{p,2} \left((\mathbf{v}_q - \mathbf{v}_p)^T \mathbf{n}_{pq}^\perp \right) \left((R_p^* + R_q^*) - R_{p,q} \right)^+ \mathbf{n}_{pq}^\perp \right] \end{aligned}$$

Pedestrian Traffic Model

Cost functional for pedestrian p :

$$J_p(\mathbf{u}_p) = \int_{t_0}^{\infty} e^{-\eta_p s} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] ds$$

where

Pedestrian Traffic Model

Cost functional for pedestrian p :

$$J_p(\mathbf{u}_p) = \int_{t_0}^{\infty} e^{-\eta_p s} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] ds$$

where

- $L_{p,1} = \frac{1}{2} (\mathbf{v}_p^* - \mathbf{v}_p)^T (\mathbf{v}_p^* - \mathbf{v}_p)$
 \Rightarrow cost of drifting from optimal velocity

Pedestrian Traffic Model

Cost functional for pedestrian p :

$$J_p(\mathbf{u}_p) = \int_{t_0}^{\infty} e^{-\eta_p s} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] ds$$

where

- $L_{p,1} = \frac{1}{2} (\mathbf{v}_p^* - \mathbf{v}_p)^T (\mathbf{v}_p^* - \mathbf{v}_p)$
 \Rightarrow cost of drifting from optimal velocity
- $L_{p,2} = \sum_{q \neq p} e^{-D_{pq}/R_p^0}$
 \Rightarrow cost of discomfort from walking too near to other pedestrians

Pedestrian Traffic Model

Cost functional for pedestrian p :

$$J_p(\mathbf{u}_p) = \int_{t_0}^{\infty} e^{-\eta_p s} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] ds$$

where

- $L_{p,1} = \frac{1}{2} (\mathbf{v}_p^* - \mathbf{v}_p)^T (\mathbf{v}_p^* - \mathbf{v}_p)$
 \Rightarrow cost of drifting from optimal velocity
- $L_{p,2} = \sum_{q \neq p} e^{-D_{pq}/R_p^0}$
 \Rightarrow cost of discomfort from walking too near to other pedestrians
- $L_{p,3} = \theta_p \left(\mathbf{u}_p^T \mathbf{e}_p \right)^2 + (1 - \theta_p) \left(\mathbf{u}_p^T \mathbf{e}_p^\perp \right)^2$
 \Rightarrow cost of accelerating/decelerating/turning

Pedestrian Traffic Model

Hamiltonian:

$$H(t, \mathbf{x}, \boldsymbol{\lambda}, \mathbf{u}) = e^{-\eta_p t} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] + \boldsymbol{\lambda}^T \mathbf{f}$$

Pedestrian Traffic Model

Hamiltonian:

$$H(t, \mathbf{x}, \boldsymbol{\lambda}, \mathbf{u}) = e^{-\eta_p t} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] + \boldsymbol{\lambda}^T \mathbf{f}$$

Applying the maximum principle yields:

$$\mathbf{u}_p^* = -\frac{1}{c_{p,3}} e^{-\eta_p t} M_p \boldsymbol{\lambda}_{\mathbf{v}_p}$$

Pedestrian Traffic Model

Hamiltonian:

$$H(t, \mathbf{x}, \boldsymbol{\lambda}, \mathbf{u}) = e^{-\eta_p t} [c_{p,1} L_{p,1} + c_{p,2} L_{p,2} + c_{p,3} L_{p,3}] + \boldsymbol{\lambda}^T \mathbf{f}$$

Applying the maximum principle yields:

$$\mathbf{u}_p^* = -\frac{1}{c_{p,3}} e^{-\eta_p t} M_p \boldsymbol{\lambda}_{\mathbf{v}_p}$$

and solving the adjoint dynamics for \mathbf{v}_p results in

$$\mathbf{u}_p^* = M_p \left[I - \frac{1}{\eta_p} \left(\frac{\partial \mathbf{v}_p^*}{\partial \mathbf{r}_p} \right)^T \right] \left(\frac{\mathbf{v}_p^* - \mathbf{v}_p}{\tau_p} \right) - A_p^0 M_p \left[\frac{\partial L_{p,2}}{\partial \mathbf{r}_p} + \eta_p \frac{\partial L_{p,2}}{\partial \mathbf{v}_p} \right]$$

where

$$M_p = \frac{1}{2} \left[\theta_p \mathbf{e}_p \mathbf{e}_p^T + (1 - \theta_p) \mathbf{e}_p^\perp \left(\mathbf{e}_p^\perp \right)^T \right]^{-1}, \quad \tau_p = \frac{\eta_p c_{p,3}}{c_{p,1}}, \quad A_p^0 = \frac{c_{p,2}}{\eta_p^2 c_{p,3}}$$

Let's go to the tape....

Model Parameters

The model contains several (seemingly arbitrary) parameters:

- R_p^* - physical radius of pedestrians
- R_p^0 - spatial discount factor
- η_p - temporal discount factor
- $k_{p,1}$ } weighting factors for inter-pedestrian interactions
- $k_{p,2}$ }
- $c_{p,1}$ } weighting factors for costs functions
- $c_{p,2}$ }
- $c_{p,3}$ }
- c_p^+ } weighting factors for longitudinal/latitudinal discomfort
- c_p^- }
- θ_p - relative weight of longitudinal vs. latitudinal acceleration

- Eliminate simplifying assumptions in model
 - Introduce cooperation between pedestrians
 - Expand anisotropy property of pedestrians
 - Limit pedestrians' knowledge of the current state
- Study of parameter values
 - Macroscopic data vs. microscopic data
 - Relationship between parameters and outputs within model
- Examine how variations in environment influence behavior

References

- ① Hoogendoorn, S. P., Bovy, P. H. L. Simulation of pedestrian flows by optimal control and differential games. *Optimal Control Applied Methods*. 24:153-172. 2003.
- ② Burns, J. A. *The Calculus of Variations and Control with Modern Applications*. Boca Raton: CRC. 2014.
- ③ Isaacs, R. *Differential Games: A Mathematical Theory with Applications to Warfare and Pursuit, Control and Optimization*. New York: Wiley. 1965.
- ④ Evans, L. C. *An Introduction to Mathematical Optimal Control Theory*. 2nd Ed. University of California, Berkeley.
- ⑤ Hoogendoorn, S. P., Bovy, P. H. L. Pedestrian route-choice and activity scheduling theory and models. *Transportation Research Part B*. 38:169-190. 2004.
- ⑥ Hughes, R. L. A continuum theory for the flow of pedestrians. *Transportation Research Part B*. 36:507-535. 2002.
- ⑦ Johnson, P. A. Numerical Solution Methods for Differential Game Problems (Master's thesis). Massachusetts Institute of Technology, Cambridge, MA. 2007.